



Marine Rubber Tire Gantry

35 - 600 ton capacity

The Hoist Marine Rubber Tire Gantry (RTG) carefully transports boats (35-600 tons) on land, and in and out of the water. Designed to complement Hoist's Neptune Series marina forklift, the Hoist Marine RTG features premium standard components, maximum corrosion protection and advanced technology.

KEY FEATURES

HOIST HEIGHT PERFORMANCE

Obtain full lifting height to the top without risking damage to the lift or load.

ARTICULATED PIVOT TRUNION

Relieves stress on frame from uneven surfaces, preventing structural damage.

SUPERIOR ERGONOMIC CONTROLS

Designed to provide the operator maximum comfort to reduce fatigue. Ergonomic controls provide easy, efficient and safe operation.

WIRELESS REMOTE CONTROL

Provides full control away from the boat hoist, giving the operator freedom to move to any location around the machine.

4-PLY NYLON SLINGS

The durable nylon slings provide excellent durability, safety and reliability. Spreaders, slings, chine and keel pads standard.

POWERED SLING ADJUSTMENT

Easily move the sling to adjust to the load. Easy maintenance with no lubrication required.

ALL-WHEEL STEERING*

Provides precise maneuverability and tight turning radius within limited areas.

QUAD WINCH DESIGN & QUAD CORNER CONTROL

Provides increased lift speeds while the independent control at all four corners provides precise movements of the boat forward/backward and left/right.

*Optional feature



HOIST LEVELING SYSTEM

Prevents damage to the load due to sling overload. Standard load indicator gauges located on operator platform.

CORROSION-RESISTANT PACKAGE

Stainless steel tubing and zinc-coated fasteners and pins for maximum corrosion protection. Three-step paint process – moisture-cure zinc rich primer; catalyzed epoxy primer; and high performance gloss urethane – provides superior protection from fresh and salt water environments.

UV PROTECTION SLEEVES

Hoses are protected from UV rays, corrosion and abrasions.

MODULAR HEAVY-DUTY FRAME CONSTRUCTION

Bolted-flange design allow for easy and quick reconfiguration.

6499 W. 65th Street | Bedford Park, Illinois 60638 USA

P: 800.367.5600 | 708.458.1176 | F: 708.458.1176

www.hoistlift.com